

MITSUBISHI FUSO JAPAN

FN EURO 3



6x4 Rigid Truck & Prime Mover | 280hp | max. GCW 60 tons



EURO III



**Air Suspension
Seats**



**Most
Fuel Efficient**



**Comfortable
Cabin**



**100% Japanese
Durable chassis**



UAN - 111-MASTER (111 627 837)
www.mmcl.com.pk



*APPLICATIONS



Cargo



Tanker



Garbage Collector



Fire Fighting Truck



Cargo with Crane



Van





Dump Truck



Troop Truck

MASS DATA		FN-62 RIGID Truck 6X4	FNP-62 PRIME MOVER 6X4
GVW/GCW (Kg)		28,000	60,000
Kerb Weight (Kg)		6,900	6,800
Payload (kg (GVW-Kerb Weight)		21,100	53,200
ENGINE			
Make		FUSO	FUSO
Model Configuration		6M60-1AT2	6M60-1AT2
Configuration		6 in-line	6 in-line
Type:		4 Stroke, water cooled direct injection turbo charged with intercooler, diesel engine - Common Rail	4 Stroke, water cooled direct injection turbo charged with intercooler, diesel engine - Common Rail
Engine Output (ps)		280 @ 2,400	280 @ 2,400
Engine Torque (kgf.m)		90 @ 1,450	90 @ 1,450
Engine Displacement (cc)		7,545	7,545
Euro Emission		EURO III	EURO III
PERFORMANCE			
Maximum Speed (km/hr)		100	90
Gradeability (%)		36	19.5
Turning Radius (m)		8.7	6.7
Ground Clearance (mm)		260	260
GEARBOX			
Make / Model		EATON - ES 11109 (9 + 1)	EATON - ES 11109 (9 + 1)
High & Low Ratios		12.637 - 1.0	12.637 - 1.0
Reverse		13.21	13.21
Final Gear Ratio		5.857	5.857
AXLE			
Front Axle		Reverse Elliot "I" beam	Reverse Elliot "I" beam
Rear Axle		Full Floating Type, Single Reduction Hypoid Gear	Full Floating Type, Single Reduction Hypoid Gear
SUSPENSION			
Front		Semi-elliptical Laminated Leaf Springs with Double Acting Telescopic Shock Absorbers. 1400x80x12 - 10	Semi-elliptical Laminated Leaf Springs with Double Acting Telescopic Shock Absorbers. 1400x80x12 - 10
Rear		Inverted & Laminated Leaf Springs with trunnion base and radius rods Main: 1,320x90x22 - 8 Helper: 1,320x90x20 - 2	Inverted & Laminated Leaf Springs with trunnion base and radius rods Main: 1,320x90x22 - 8 Helper: 1,320x90x20 - 2
CHASIS FRAME			
Type		Ladder type, Channel Section	Ladder type, Channel Section
CLUTCH			
Type		Hydraulic, Coil spring type, single dry plate with air pressure assistance	Hydraulic, Coil spring type, single dry plate with air pressure assistance
Size (mm)		C7W38 (380)	C7W38 (380)
STANDARD BRAKE SYSTEM			
Service (Standard)		Air over hydraulic with dual circuit	Air over hydraulic with dual circuit
Parking		Internal Expanding type on Propeller Shaft	Internal Expanding type on Propeller Shaft
Auxiliary		Exhaust Brake	Exhaust Braket
Braking System (Optional)		Full air brakes (ABS) & auto slack adjuster	Full air brakes (ABS) & auto slack adjuster
TYRES			
Front		11.00 R20	11.00 R20
Rear		11.00 R20	11.00 R20
FUEL TANK			
Capacity (Liters)		400	400
DIMENSIONS			
WB Wheelbase (mm)		5,460	4,560
OL Overall Length (mm)		8,500	6,695
OW Overall Width (mm)		2,455	2,455
OH Overall Height (mm)		2,700	2,700
CF Cabin to End Frame (mm)		6,430	4,625



UAN # MASTER (021-111-627-837)
www.fusomaster.com



KARACHI

Head Office
UAN: 111-MASTER (111 627 837)
FUSO Master Motor Pvt. Ltd
Tel: 021-32554146-7, 0302-8203021
0301-8504124
FUSO Master Karachi Motors
Tel: 021-34937733, 0321-2626944

QUETTA

FUSO Master Quetta Motors
Tel: 0321-6969690, 0300-6969690

MULTAN

FUSO Master Multan Motors
Tel: 0300-0670577, 0300-8735129
0302-8203025

FAISALABAD

Fuso Master Al Noor Motors
Tel: 0301-8262988

LAHORE

FUSO Master Motor Corp. Pvt. Ltd
Cell: 0302-8203027, 0302-8285535

ISLAMABAD

Master Capital Motors
Tel: 051-2226840-41, 0301-8260213
0300-8560508

PESHAWAR

FUSO Master Peshawar Motors
Tel: 091-5580098-99, 0301-8227651
0300-5594445